

SHOCK TYPE: SHOCK65 IMPACT14 Shock absorber KTM-Husqvarna-GAS GAS 65						
INTERNAL SHIMS SETTING			RECOMMENDED SPRING RATE			
COMPRESSION	REBOUND	HIGH SPEED	Rider weight	Spring rate		
ID 12	ID 12	ID 6	18-25 Kg	K 3.5		
3x30x020	2x27x020	2x17x020	26-34 Kg	K 4.0 (Stock rate)		
25x010	20x015	12x010	35-43 Kg	K 4.4		
18x015	27x020	17x020	44-52 Kg	K 4.8		
30x015	25x020	14x020	NOTES			
28x020	23x020	11x020	* For the best results there a 15-20% of possibility that the inner valving needs to be changed.			
26x020	21x020					
24x020	18x025		** For the best results there a 30-35% of possibility that the inner valving needs to be changed.			
22x025	16x020					
20x020			Static SAG	28-30 mm		
18x025			Oil Viscosity	SAE 5.0		
16x020			Nitrogen Pressure	10 bar		
ADJUSTERS			STANDARD SETTING			
RIDER WEIGHT			18-25 Kg	26-34 Kg	35-43 Kg	44-52 Kg
Compression Low speed (basic setting from full in to open)			32 click	22 click	15 click *	10 click **
Compression High speed (basic setting from full in to open)			6 turns	4 turns	3 turns *	2 turns **
Rebound (basic setting from full in to open)			24 click	22 click	20 click *	18 click **